**Applicant:** Richard Munz **Application No.:** Not Yet Known

## IN THE CLAIMS

1. (Currently amended) A cleaning device (1, 1') for printing cylinders and printing plate cylinders of rotary presses comprising a guide rail (2), which is arranged generally parallel to the printing cylinder and on which a washing device (4) is guided, wherein the washing device (4) has at least one rotationally driven cleaning brush (8) with at least one axis of rotation arranged approximately [[axis-]]parallel to the printing cylinder, wherein the washing device (4) is held on a longitudinal side of the guide rail (2) facing the printing cylinder so that the washing device can move and the axis of rotation of the at least one cleaning brush (8) is arranged between planes formed by a top side and a bottom side of the guide rail (2).

- 2. (Currently amended) Cleaning device according to the preamble of Claim 1, characterized in that wherein the rotational drive (3) allocated to the at least one cleaning brush (8) is arranged in a circular envelope formed by an outer periphery of the cleaning brush.
- 3. (Currently amended) Cleaning device according to <u>Claim 2</u>, <u>wherein Claim 1 or 2</u>, <u>characterized in that</u> the rotational drive (3) is formed as an electric drive integrated into the at least one cleaning brush (8).
- 4. (Currently amended) Cleaning device according to <u>Claim 2</u>, <u>wherein one of Claims 1 to 3</u>, <u>characterized in that</u> the rotational drive (3) is arranged at least in regions within a brush body <del>preferably</del> with cleaning bristles for the at least one cleaning brush (8).

Applicant: Richard Munz

**Application No.:** Not Yet Known

5. (Currently amended) Cleaning device according to Claim 2, wherein one of

Claims 1 to 4, characterized in that a rotor of the rotational drive (3) is formed as a

brush body.

6. (Currently amended) Cleaning device according to Claim 1, wherein one of the

preceding claims, characterized in that the a brush body of the cleaning brush is

guided locked in rotation on a rotationally driven shaft (10) and displaceable or

movable in a longitudinal direction.

7. (Currently amended) Cleaning device according to Claim 1, wherein one of

Claims 1 to 6, characterized in that at least one of the guide rail and [[/or]] the

washing device are produced from an extruded section and especially from an

aluminum extruded section.

- 3 -